

طول الأرضيات المكتبية


أرضيات مكتبية Carpet Tiles



Coal 10




Chocolate 10



Aqua 10



Beige 10



Charcoal 10



Bespin

Use Classification

Medium Commercial / Class 32

Product Description	Medium Commercial PP Tufted Loop Pile Bitumen Tile	
Recycled Content	n/a	
Fibre Type	Stainproof Miracle Fibre - Polypropylene	
Fibre Mass	±515g/m ² (±15)	±15.18 oz/yd ² (±0.44)
Pile Height	± 4mm (±0.5)	±0.16in (±0.02)
Total Thickness	±6.0mm (±0.5)	±0.24in (±0.02)
Total Mass **	±3892g/m ² (±5%)	±114.78 oz/yd ² (±5%)
MTO Sizes (tile)	50x50cm	19.69x19.69(in)
MTO Backing Options	NexBac (NB)	
Machine Gauge	1/10"	
Stitch Rate	35 stitches/10cm	
Fire Classification	Bfl -s1	
Colour Fastness to:		
Light	> 6.0	(NF EN ISO 105-BO2)
Rubbing (staining)	4-5	(ISO 105-X12)
Water (staining)	4-5	(ISO 105-EO1)
Electrostatic Propensity: Body voltage	≤ 2.0 kV	(ISO 6356: 2012)
Sound Absorption	aw: 0.15	(ISO 354: 2023)
Sound Insulation	25dB	(ISO 10140-3: 2021)
Thermal Resistance	0.0740 m ² .KW	(ISO 8302: 2001)
Dimensional Stability	≤ 0.2%	(ISO 986: 2006)
VOC Emissions (GBCSA/ GBCA & CRI Specifications)	Passed	(ASTM D5116: 2017)
Castor Chair Suitability	Occasional Use	(NF EN 985 – Method A)
Guarantee	15 years	
Warranty	5 years	
** Weighted Average		

