

ICONIK 240

Datasheet

| Classification | Norm | Tarkett Value |
|--|----------------|--|
| Product type | EN ISO 26986 | Expanded (cushioned) poly(vinyl chloride) floor covering |
| Domestic classification | EN ISO 10874 | 23 Heavy |
| Commercial classification | EN ISO 10874 | 32 General |
| Industrial classification | EN ISO 10874 | 41 Moderate |
| Binder content | ISO 11638 | Type I |
| Technical Characteristics | Norm | Tarkett Value |
| Total thickness | ISO 24346 | 2,40 mm |
| Wear layer thickness | ISO 24340 | 0,35 mm |
| Total weight | ISO 23997 | 1580 g/m ² |
| Performance for CE Marking | Norm | Tarkett Value |
| Declaration of Performance # | EN 14041 | 0007-0023-DOP-2020-01 |
| Reaction to fire | EN 13501-1 | Cfl-s1 |
| Slip resistance | EN 13893 | Class DS ($\mu \geq 0,30$) |
| Slip resistance | DIN 51130 | R10 |
| Static Electrical Propensity | EN 1815 | Antistatic (≤ 2 kV) |
| Thermal resistance | ISO 10456 | 0,030 m ² •K/W |
| Technical Performance | Norm | Tarkett Value |
| Residual indentation | EN ISO 24343-1 | Required value: $\leq 0,20$ mm |
| Castor chair | ISO 4918 | No damage |
| Impact sound reduction - ΔL_w | EN ISO 717-2 | 16 dB |
| Colour fastness to light | ISO 105-B02 | ≥ 6 |
| Chemical resistance | ISO 26987 | Not affected |
| Underfloor heating | | Suitable (subfloor temperature maximum 27°C) |
| Dimensional stability | EN ISO 23999 | Average measured value : ≤ 0.20 % |
| Sustainability performances | Norm | Tarkett Value |
| Recyclability through ReStart® | | Recyclable |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) | | 5,43 kg CO ₂ eq /m ² |
| Total VOC Emissions | EN 16516 | Gold (≤ 100 $\mu\text{g} / \text{m}^3$) |
| Formaldehyde emission | | E1 |
| Dimensions and designs | | |
| Roll | | Roll 2 x 25 m Roll 3 x 25 m Roll 4 x 25 m |
| Number of designs available | | 131 |



The above information is subject to modification for the benefit of further improvement (09/12/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.