


طول الأرضيات المكتبية


أرضيات مكتبية Carpet Tiles



AD08 2032
712137002



AD08 9532
712137011



AD08 9513
712137010




AD08 8913
712137009



AD08 7803
712137008



Type of manufacture	ISO 2424		Tufted 1/10 "					
Aspect	ISO 2424		Structured loop pile					
Dye method			Solution dyed					
Dimension	EN ISO 24342	cm x cm	50 x 50 / 19,68" x 19,68" (20 tiles per box)					
Primary backing	ISO 2424		Polyester fleece					
Secondary backing	ISO 2424		ProBase - modified bitumen.					
Pile fibre composition	ISO 2424		BCF Polyamide 6					
Total thickness	ISO 1765	mm	6,5	inch	0,3			
Effective pile thickness	ISO 1766	mm	3,4	inch	0,13			
Total mass	ISO 8543	g/m ²	4000	oz/yd ²	118,1			
Total pile mass	ISO 2424	g/m ²	580	oz/yd ²	17,1			
Effective pile mass	ISO 8543	g/m ²	380	oz/yd ²	11,2			
Pile density	ISO 8543	g/cm ³	0.112	lb/in ³	0,0040			
Number of tufts	ISO 1763	/dm ²	1580	/yd ²	132104			
Stroll test	ISO 6356	kV	≤ 2,0					
Vertical resistance	ISO 10965	Ohm	-					
Horizontal resistance	ISO 10965	Ohm	-					
Use classification	EN 1307		33 Commercial - heavy use					
Luxury rating	EN 1307		LC 1					
Dimensional stability	EN 986	%	≤ 0,2					
Impact sound reduction ΔL_w	ISO 10140	dB	25					
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
		α_s	0.00	0.02	0.06	0.17	0.29	0.37
Noise reduction	ISO 354	α_w	0.20					
Thermal resistance	ISO 8302	m ² .K/W	0.078					
Flammability	EN 13501-1		Bfl - s1 (loose laid tested)					
Prodis - GUT	www.pro-dis.info		AEB3E85F					





EN 14041
0493-CPR-0002


Manufactured by:


Tarkett BV
Taxandriaweg 15
NL - 5142 PA Waalwijk










































DESSO flooring products are to be installed in full accordance with Tarkett's installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20240528

Tarkett BV
Taxandriaweg 15
NL-5142 PA Waalwijk



